

lbex cases made with rugged molded polypropylene comes in a range of sizes that are suitable for outdoor rugged environments. They are dustproof, water tight, temperature resistant from -20 to 80° C (-4 to 176° F) and comes with pressure release valve to protect pressure sensitive instruments. Removable, customizable pre-cut cube foams and wave foams are included with the case.

MODEL	EXTERIOR DIMENSIONS (L x W x H)	INTERIOR DIMENSIONS (L x W x H)	LID DEPTH	BASE DEPTH	WEIGHT
IC-1100BK	8.3 x 6.6 x 3.5" (210 x 168 x 90mm)	7.3 x 4.8 x 3.0" (186 x 124 x 75mm)	0.4" (10mm)	2.6" (65mm)	1.1 lb (0.5 kg)
IC-1100YL	8.3 x 6.6 x 3.5" (210 x 168 x 90mm)	7.3 x 4.8 x 3.0" (186 x 124 x 75mm)	0.4" (10mm)	2.6" (65mm)	1.1 lb (0.5 kg)
IC-1300BK	13.0 x 11.0 x 4.7" (330 x 280 x 121mm)	11.8 x 8.7 x 4" (300 x 220 x 100mm)	1.1" (28mm)	2.9" (73mm)	3.3 lb (1.5 kg)
IC-1300YL	13.0 x 11.0 x 4.7" (330 x 280 x 121mm)	11.8 x 8.7 x 4" (300 x 220 x 100mm)	1.1" (28mm)	2.9" (73mm)	3.3 lb (1.5 kg)
IC-1500BK	16.9 x 15.0 x 6.1" (430 x 380 x 155mm)	15.5 x 12.6 x 5.6" (395 x 320 x 144mm)	1.4" (35mm)	4.2" (108mm)	6 lb (2.7 kg)
IC-1500YL	16.9 x 15.0 x 6.1" (430 x 380 x 155mm)	15.5 x 12.6 x 5.6" (395 x 320 x 144mm)	1.4" (35mm)	4.2" (108mm)	6 lb (2.7 kg)
IC-1800BKW	21 x 14.0 x 8.8" (530 x 354 x 225mm)	20.1 x 11.5 x 6.8" (510 x 292 x 174mm)	1.8" (45mm)	5.1" (130mm)	10.2 lb (4.6 kg)
IC-1800YLW	21 x 14.0 x 8.8" (530 x 354 x 225mm)	20.1 x 11.5 x 6.8" (510 x 292 x 174mm)	1.8" (45mm)	5.1" (130mm)	10.2 lb (4.6 kg)
IC-2100BK	20.3 x 16.3 x 7.9" (515 x 416 x 200mm)	19.1 x 14.0 x 7.3" (485 x 355 x 185mm)	3.1" (80mm)	4.2" (108mm)	9 lb (4.08 kg)
IC-2100YL	20.3 x 16.3 x 7.9" (515 x 416 x 200mm)	19.1 x 14.0 x 7.3" (485 x 355 x 185mm)	3.1" (80mm)	4.2" (108mm)	9 lb (4.08 kg)

Replacement Parts

DESCRIPTION
Replacement foam set for IC-1100 Case
Replacement foam set for IC-1300 Case
Replacement foam set for IC-1500 Case
Replacement foam set for IC-1800 Case
Replacement foam set for IC-2100 Case
Replacement wheel for IC-1800



