

AC/DC ADAPTERS - SWITCHING

- Universal Input voltage – 100-240VAC 50/60 Hz
- Regulated output with low ripple noise
- Short circuit, over voltage and over current protection
- Energy efficiency Level V
- cULus approved

Circuit-Test offers a full range of AC/DC switching power supplies that meet Energy efficiency Level V requirement and are also certified with North American safety approval cULus. These external power supplies are available in compact lightweight Wall mount style and also in versatile Desktop style; suitable for Telecommunication, Computer, Industrial Controller and other electronic applications. Large inventory of all stocking models is available in our warehouse or custom manufacturing (with minimums) is also available with short lead times.

Compact Wall Mount Power Supplies

MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	PLUG SIZE	CENTRE POLARITY
RPR-051A5-P5	5VDC	1.5A	2.1 x 5.5mm	+
RPR-051A5-UMB	5VDC	1.5A	Micro USB plug	
RPR-053A0-P5	5VDC	3.0A	2.1 x 5.5mm	+
RPR-053A0-UMB	5VDC	3.0A	Micro USB plug	
RPR-063A0-P5	5.9VDC	3.0A	2.1 x 5.5mm	+
RPR-061A2-P5	6VDC	1.2A	2.1 x 5.5mm	+
RPR-091A5-P3	9VDC	1.5A	1.3 x 3.5mm	+
RPR-092A2-P5	9VDC	2.2A	2.1 x 5.5mm	+
RPR-09600-P5	9VDC	600mA	2.1 x 5.5mm	+
RPR-1201A6-N5	12VDC	1.6A	2.1 x 5.5mm	-
RPR-1201A6-P5	12VDC	1.6A	2.1 x 5.5mm	+
RPR-1201A6-P6	12VDC	1.6A	2.5 x 5.5mm	+
RPR-1202A0-P5	12VDC	2.0A	2.1 x 5.5mm	+
RPR-1203A0-P5	12VDC	3A	2.1 x 5.5mm	+
RPR-1205A0-P5	12VDC	5A	2.1 x 5.5mm	+
RPR-12600-P5	12VDC	600mA	2.1 x 5.5mm	+
RPR-1501A3-P5	15VDC	1.3A	2.1 x 5.5mm	+
RPR-1801A1-P5	18VDC	1.1A	2.1 x 5.5mm	+
RPR-2401A0-P5	24VDC	1.0A	2.1 x 5.5mm	+
RPR-2402A5-P5	24VDC	2.5A	2.1 x 5.5mm	+
RPR-24500-N5	24VDC	500mA	2.1 x 5.5mm	-
RPR-24500-P5	24VDC	500mA	2.1 x 5.5mm	+
RPR-24800-P5	24VDC	800mA	2.1 x 5.5mm	+

Compact Desktop Power Supplies

MODEL	OUTPUT VOLTAGE	OUTPUT CURRENT	PLUG SIZE	CENTRE POLARITY	POWER CORD
RPT25-05-P5-A2	5VDC	5.0A	2.1 x 5.5mm	+	138-201
RPT40-12-P5-A3	12VDC	3.3A	2.1 x 5.5mm	+	138-406
RPT60-12-P5-A3	12VDC	5.0A	2.1 x 5.5mm	+	138-406
RPT90-12-P5-A3	12VDC	7.0A	2.1 x 5.5mm	+	138-406
RPT108-12-P5-A3	12VDC	9.0A	2.1 x 5.5mm	+	138-406
RPT192-12-D4-A3	12VDC	16A	4Pin DIN		138-406
RPT50-15-P5-A3	15VDC	3.3A	2.1 x 5.5mm	+	138-406
RPT50-18-P5-A3	18VDC	2.7A	2.1 x 5.5mm	+	138-406
RPT90-19-P5-A3	19VDC	4.7A	2.1 x 5.5mm	+	138-406
RPT50-24-P5-A3	24VDC	2.1A	2.1 x 5.5mm	+	138-406
RPT65-24-P5-A3	24VDC	2.7A	2.1 x 5.5mm	+	138-406
RPT90-24-P5-A3	24VDC	3.7A	2.1 x 5.5mm	+	138-406
RPT120-24-P5-A3	24VDC	5.0A	2.1 x 5.5mm	+	138-406
RPT200-24-D4-A3	24VDC	8.3A	4Pin DIN		138-406

