

MULTIMETERS - DIGITAL

DMM - Industrial, True RMS, 6000 Count, CAT IV

- 6000 count LCD display
- Backlight and Bargraph
- High voltage AC/DC to 1000V
- AC/DC current to 10A
- Resistance to 60M Ω
- Capacitance to 1000uF
- Temperature to 1382°F
- Frequency to 40MHz
- Min / Max / Relative / Data Hold
- Continuity and Diode test
- Double Moulded Waterproof housing
- Test leads, Temperature probe and Battery included



MODEL	DESCRIPTION
DMR-6780	DMM - Industrial, True RMS, 6000 Count, CAT IV

DMM - Industrial, True RMS, 4000 Count, CAT IV

- 4000 count LCD with Backlight
- High voltage AC/DC to 1000V
- AC/DC current to 10A
- Resistance to 40M Ω
- Capacitance to 100uF
- Temperature to 1382°F
- Frequency to 10MHz
- Relative / Data Hold
- Continuity and Diode test
- Double Moulded Waterproof housing
- Test leads, Temperature probe and Battery included



MODEL	DESCRIPTION
DMR-6700	DMM - Industrial, True RMS, 4000 Count, CAT IV

DMM - Large LCD, Manual ranging, CAT IV

- 2000 count LCD with Backlight
- Extra Large Digits
- High voltage DC to 1000V
- AC Voltage to 700V
- High current AC/DC to 20A
- Resistance to 200M Ω
- Capacitance to 200uF
- Continuity and Diode Test
- Test leads and Battery included



MODEL	DESCRIPTION
DMR-6600	DMM - Large LCD, Manual ranging, CAT IV

DMM - Compact, Autoranging, True RMS

- 6000 count LCD display
- Backlight and Bargraph
- AC/DC voltage to 1000V
- AC/DC current to 10A
- Resistance to 60M Ω
- Capacitance to 4000uF
- Temperature to 1400°F
- Frequency to 10MHz
- Min /Max / Data Hold
- Continuity and Diode test
- Test leads, Temperature probe and Battery included



MODEL	DESCRIPTION
DMR-6550	DMM - Compact, Autoranging, True RMS

DMM - Compact, Autoranging

- 4000 count LCD display
- AC/DC voltage to 600V
- AC/DC current to 10A
- Resistance to 40M Ω
- Capacitance to 200uF
- Temperature to 1400°F
- Frequency to 10MHz
- Relative / Data Hold
- Auto Power Off
- Continuity and Diode test
- Test leads, Temperature probe and Battery included



MODEL	DESCRIPTION
DMR-6500	DMM - Compact, Autoranging

DMM - Autoranging, Pocket Size, CAT IV

- 4000 count LCD display
- Compact pocket size
- Built-in Flashlight
- Non-contact voltage detector
- AC/DC voltage to 600V
- AC/DC current to 200mA
- Resistance to 40M Ω
- Capacitance to 200uF
- Frequency to 10kHz
- Built-in Test leads and Batteries included



MODEL	DESCRIPTION
DMR-602	DMM - Autoranging, Pocket Size, CAT IV