

### Nail Down Clips



MODEL	SIZE	PKG QTY
7601-C	3.5mm	100
7604-C	6mm	100
7605-C	7mm (RG59)	100
7606-C	8mm (RG6)	100
7607-C	9mm	100

### Strain Reliefs



MODEL	DESCRIPTION	SIZE	PKG QTY
34-622-50	Bushing	3/8"	50
34-623-50	Bushing	1/2"	50
34-624-50	Bushing	5/8"	50
3P-B-8	Strain Relief	7/16"	8
3P-B-C	Strain Relief	7/16"	100
6P-B-6	Strain Relief	5/8"	6
6P-B-C	Strain Relief	5/8"	100

### Wire Clamps

For one-piece bundling and mounting. Made of clear nylon with smooth internal edges. Easy-to-read bundle diameters are molded in. Meets UL 94V-2 flammability classification.



MODEL	SIZE	PKG QTY
7118LN-C	1/8"	100
7119LN-C	3/16"	100
7120LN-C	1/4"	100
7122LN-C	3/8"	100
7124LN-C	1/2"	100
7126HN-C	5/8"	100
7128HN-C	3/4"	100
7130HN-C	1"	100
7133HN-C	1-1/4"	100
7135HN-C	1-1/2"	100

### Grommets

Flexible, oil-resistant vinyl grommets. Inserted into pre-drilled holes, they protect wire and cable from sharp corners and edges.



MODEL	SIZE	PKG QTY
6115-C	1/4" OD x 1/8" ID	100
6116-C	5/16" OD x 3/16" ID	100
6117-C	3/8" OD x 1/4" ID	100
6118-C	7/16" OD x 5/16" ID	100
6119-C	1/2" OD x 3/8" ID	100
6120-C	5/8" OD x 1/2" ID	100

### Barrier Strips - European Style

#### CIRCUIT-TEST

12-pole terminal blocks constructed of Nylon66 material. Captive steel screws for wire fastening; tin-plated zinc alloy contacts. Can be cut into sections. Rated from -37 to + 110°C.



MODEL	WIRE SIZE	POWER RATING	DIMENSIONS	APPROVAL
PA08DS	12-22 AWG	20A/600V	96 x 16 x 13mm	UL
PA10DS	12-22 AWG	30A/600V	118 x 20 x 16mm	UL
PA12DS	10-22 AWG	35A/600V	141 x 24 x 20mm	UL US
PA14DS	8-20 AWG	50A/600V	158 x 26 x 26mm	UL US

### Terminal Blocks

Screw terminals mounted in molded monoblock phenolic.



MODEL	POLES	SCREW TERMINALS	WIRE SIZE	POWER RATING
2140-P	2	6-32	16AWG	15A / 250VAC
2142-P	2	8-32	10AWG	30A / 250VAC
4140-P	4	6-32	16AWG	15A / 250VAC
4142-P	4	8-32	10AWG	30A / 250VAC
6140-P	6	6-32	16AWG	15A / 250VAC
6142-P	6	8-32	10AWG	30A / 250VAC
8140-P	8	6-32	16AWG	15A / 250VAC
8142-P	8	8-32	10AWG	30A / 250VAC
10140-P	10	6-32	16AWG	15A / 250VAC
12140-P	12	6-32	16AWG	15A / 250VAC

### OPTIONAL JUMPERS

Jumpers designed for use with bus terminals.




MODEL	POWER RATING	PKG QTY
140J1-4	15A / 250VAC	4
140J1-20	15A / 250VAC	20
142J1-P-3	30A / 250VAC	3

### PCB Terminals

#### CIRCUIT-TEST

PCB-mount terminal block constructed of Nylon66 material. Steel screws, tin-plated alloy contacts. Interlocking, with 5.08mm (0.2") spaced leads. Rated at 10A / 125VAC.



MODEL	DESCRIPTION	PKG QTY
PA02-10	2 Position	10
PA02-100	2 Position	100
PA03-10	3 Position	10
PA03-100	3 Position	100