

Coolers and Blowers

CABINET COOLER

- Air movement: 20 CFM
- Sound level: 24 dBA
- Includes power supply: 12VDC / 100mA
- Power supply has 6' cord

Removes heat generated by components located in smaller cabinets and entertainment centers. Operating only when needed to minimize dust, this quiet cooling device features an aesthetically designed vent that can be painted to suit the decor. The quiet, internal fan activates automatically when temperatures generated by hot-running equipment reach damaging levels.



| MODEL | |
|----------|--|
| CAB-COOL | |

COMPONENT COOLER

- Single fan, low profile
- Air movement: 8 CFM
- Sound level: 19dBA
- Includes power supply: 7.5VDC / 70mA

Low-profile design for components on open shelving, this quiet cooler turns on automatically when heat-generating components get too hot. Place the cooler directly on top of component vents.



| MODEL | |
|-----------|--|
| COMP-COOL | |

INTAKE BLOWERS

- Supply voltage: 115 VAC
- Heavy steel construction
- Attractive 19" stainless steel grill included
- Includes permanent filter (replacement filters available)
- Comes with 6ft STJW 3-wire cord



For standard 19" rack mount. Contains a quadruplex centrifugal blower, powered by a single precision ball-bearing motor. Internal neoprene isolation mounts reduce transmission of vibration to the rack. Air intake only, to pressurize the rack with filtered air.

| MODEL | DESCRIPTION | |
|---------|-------------------------|--|
| HB2160A | Intake Blower - 160 CFM | |
| HB4500A | Intake Blower - 470 CFM | |



CLOSET COOLER

- Air movement: 50 CFM
- Sound level: 28dBA
- Includes power supply: 12VDC / 400mA
- Power supply has 6' cord

The Closet Cooler quietly removes heat from equipment racks located in telecom closets. Runs only when needed, mounts to closet doors and is available with an active exhaust & passive intake for closets with gaps, or an active exhaust & active intake for tightly sealed closets. Two solid oak vents are visible and can be stained / painted to match any decor.



| MODEL | |
|-----------|--|
| CLS-COOL2 | |

Authorized
Middle Atlantic
Distributor



Thermostats



- 125VAC, 15A
- Made in Germany



These temperature controls are used to regulate heating equipment, cooling equipment, filter fans and heat exchangers. They can also be used as switching contacts for signal devices used as low or high temperature alarms. Clip mounts onto 35mm DIN rails according to EN50022 standard (mounting rail included).

Choose from: NORMALLY CLOSED (NC) for the control of heaters and heater fans or NORMALLY OPEN (NO) for the control of cooling units, or for switching signal transmitters in case of overheating.

| MODEL | DESCRIPTION | |
|-----------------------------|--------------|--|
| NC (NORMALLY CLOSED) | | |
| SKT011409NC | NC: 32-140°F | |
| NO (NORMALLY OPEN) | | |
| SKT011419NO | NO: 30-140°F | |
| SKT011419NO-C | NO: 0-60°C | |