Home Automation

Alarm Accessories • Receiver/Transmitters



Sirens / Horns



These sirens have many applications, including but not limited to alarm systems. They all operate on 6 - 12VDC.

MODEL	SOUND LEVEL	SIZE	TONE	
SD20WS	110dB	13.3 x 14.6cm	Yelp / Steady	
SH-532	124dB	8.3 x 8.9cm	3 tones	
SH-550	128dB	4.5 x 5.7cm	Warble	

Strobe Lights





SL-126-AMBER

SI-1301-BAO/R

For general purpose signaling, these strobes feature easy 2-wire installation and low current consumption. Operating life: Xenon -300 Hours/2Million Flashes, LED - 50,000 Hours. Temperature range: -20 to 60°C.

MODEL	DESCRIPTION	
SL-126-A24CLEAR	6-24VDC Xeon - Clear	
SL-126-AMBER	6-12VDC Xeon - Amber	
SL-126-BLUE	6-12VDC Xeon - Blue	
SL-126-RED	6-12VDC Xeon - Red	
SL-1301-BAQ/R	6-14VDC LED - Red	

Photoelectric Beam Sensors

ENTRY ALERT SYSTEM

Complete, stand-alone Entry Alert System, with sensor, reflector, speaker and power supply. A ding-dong or siren sound comes from the speaker when the beam is interrupted. Beam range is



adjustable, up to 7m. All components plug into each other, so no additional hard wiring required.

MODEL	DESCRIPTION	
E-931CS22RRCQ	22 ft	

PHOTOBEAM SENSOR

Sensor for garage doors, detecting objects on a manufacturing line, etc. Sensing range 0.1 to 11m, relay output selectable, with NO/NC/COM connections. Accepts 24 to 240VAC or 12 to 240VDC. Weatherproof to IP66 standard.



MODEL	DESCRIPTION	
E-931-S35RRQ	35 ft	

PHOTOBEAM TWIN SENSORS

The E-960 series are extended range infrared detectors for perimeter security, indoors or outdoors. Built-in laser beam alignment makes setup easy. Detection range and time-interval are adjustable.



MODEL	DESCRIPTION	
E-960-D90	90 ft	
E-960-D190	190 ft	
E-960-D290	290 ft	

ENFORCER

models

RF Receiver / Transmitters

RF RECEIVER - 1 CHANNEL

ENFORCER

- Use for garage door opener, house lights, etc.
- Unsurpassed antenna matching capabilities
- · Greater tuning stability against shock and vibration
- Learns up to 15 transmitters
- Operating distance: up to 650 ft
- Frequency: 315MHz
- Operating voltage: 11 24VAC / VDC
- Screw terminals for simple connection

MODEL SK-910RBQ



• Range: up to 650ft

MODEL SK-919TD1S-UP

- Over 68 billion possible codes
- Sleek case with flashing LED transmission indicator

RF TRANSMITTER - 1 CHANNEL

- Includes 12VDC alkaline battery with key chain ring
- Compatible with SK-910R, SK-910R2 and SK-910R4 receivers





 Operates up to 500 feet (150 meters)

Fits various Enforcer

- Over 68 billion possible codes
- Sleek new case with flashing LED transmission indicator

RF TRANSMITTER - 2 CHANNEL

• Includes 12VDC alkaline battery with handsome key chain ring

MODEL	
SK-919TD2A	

Quantity pricing is available online at www.rpelectronics.com or call 1-888-921-7770